

CUB GRINDER MANUAL



WARNING

To reduce the risk of injury, all operators and maintenance personnel must read and understand these instructions before operating, changing accessories, or performing maintenance on this power equipment. All possible situations cannot be covered in these instructions. However care must be exercised by everyone using, maintaining or working near this equipment.

CONTENTS

Introduction

Applications

Function and controls

Hazards & risks

Operation

Care and preventive maintenance

Specifications

Trouble shooting

Spare parts and service

INTRODUCTION

Should service or spare parts be required, prompt and efficient service is available from our branches.

General Safety Instructions for the Operation of Power Equipment

To provide power equipment that helps the operator work safely and efficiently. The most important safety device for this or any tool is the operator. Care and good judgement are the best protection against injury.

All possible hazards cannot be covered here however we have highlighted some of the important items.

Operators should look for and obey Caution, Warning and Danger signs placed on equipment, and displayed in the workplace.

Operators should also read and follow safety instructions packed with each product.

Learn how each machine works. Even if you have previously used similar machines, carefully check out each machine before you use it. Get the "feel" of it and know its capabilities, limitations, potential hazards, how it operates, and how it stops.

APPLICATIONS

- Removing trowel marks, worn sealants, plaster, paint and surface blemishes.
- Terrazzo floors
- Finish grinding joint surfaces

FUNCTION AND CONTROLS

The CUB Floor Grinder is fitted with 2.2KW single-phase motor. The motor offers a direct drive to the grinding plate with a flexible coupling between the motor and the plate.

The shroud system of this grinder is unique in design, automatically adjusting to suit segment height and floor angle. This shroud system, when used in conjunction with an appropriate industrial vacuum unit, eliminates dust loss during grinding.

The shroud has a removable section to enable the operator to grind close up to the wall. Please note that dust loss is likely when this section is removed. The grinder comes complete with a water connection for wet grinding should this be required.

This incorporates a ball valve allowing the operator to regulate the water supply to obtain the best grinding results.

The grinder has a foldable handle, which enables it to be easily transported in the boot of most small vehicles.

The rear wheels can also be extended outward should the operator want more stability from the grinder. This requires the use of a 13 mm socket or spanner.

The operator can also raise or lower the height of the handle to maximize their comfort when using the grinder.

! ELECTRICAL HAZARDS

- ENSURE that the grinder is disconnected from electric power source and motor operation switch is in the OFF position before removing the guards or making adjustments.
- ENSURE that the area requiring grinding does not contain any "live" electrical cables, gas, water or communication services which may be damaged by the action of the unit.
- ENSURE that electrical cables and plugs are in good working condition before using the grinder.

! NOISE HAZARDS

- EXCESSIVE NOISE can lead to temporary or permanent loss of hearing.
- WEAR approved hearing protection as required by Occupational Health and Safety regulations while operating the machine to limit noise exposure.

PROTECTIVE CLOTHING

- WEAR eye protection and dust mask when working in a dusty environment.

Protective clothing and footwear may also be necessary.

! ADDITIONAL HAZARDS

- BEWARE of uneven or slippery work surfaces, which could create slips, trips and falls.
- EXERCISE care when working in the vicinity of unprotected holes or excavations.

SAFETY PRECAUTIONS IN OPERATIONS

The grinder has been designed to minimize noise and vibration levels and to provide maximum operator safety. However, incorrect use of the grinder may cause serious injury; therefore the following precautions must be taken:

1. Do not use the grinder for longer than prescribed in your local environmental working regulations, as the noise load from extensive daily use may result in hearing defects.
2. Always use protective earplugs or earmuffs, goggles, gloves and correct footwear.
3. Do not modify the grinder in any manner, or use a machine that has been modified by anyone other than the manufacturer or authorized dealer.

HAZARDS AND RISKS

GENERAL GUIDELINES

- **NEVER** allow an untrained person to operate machine without adequate instruction.
- **ENSURE** all users read, understand and follow the operating instructions.
- **SERIOUS INJURY** may result from improper or careless use of this machine.
- **USE** correct manual handling techniques when moving the surface grinder. The machine is fitted with wheels for transport.

! MECHANICAL HAZARDS

DO NOT operate the machine unless all protective guards are in place.

KEEP hands and feet clear of rotating and moving parts as they will cause injury if contacted.

- **ENSURE** both the machine and the operators are stable by setting up on a level surface. Make sure the machine does not tip over, slide or fall while in operation or unattended.
- **DO NOT** leave the machine in operation while it is unattended.
- **EXERCISE CARE** when operating the unit. Extended exposure to vibration or repetitive work actions may be harmful to hands and arms.
- **NEVER** stand on the unit while it is operating.
- **ONLY USE** the recommended grinding discs or segments. Allow the machine to cool before servicing or replacing parts, severe burns may be caused by coming in contact with hot discs or segments.
- **ENSURE** that repairs to the motor and machine are carried out by qualified personnel.

CARE AND PREVENTIVE MAINTENANCE

- Check folding handle latch periodically. This is adjustable. To adjust, loosen the lock nut on the latch and then screw in the threaded paw until satisfactory tensions has been achieved.
- Inspect the grinding discs or segments before each use.
- Check all fasteners for tightness as the machine is subject to vibration.
- Clean the underside of the unit regularly to prevent a build-up of material.
- The wheel bearings are a sealed type, and require no regular greasing.

SPECIFICATIONS

Description	FLOOR CUB GRINDER
Model	CG22
Motor Output	2200W
Power Source	Electricity, AC 220v - 240v, 50Hz, single phase
Plate Diameter	250 mm
Plate Speed	1470mm
Removable Shroud Section	Yes
Active Dust Shroud	Yes
Foldable Handle	Yes
Base Material	Epoxy coated steel
Unit Weight	50 kg

4. Do not add weight to the machine to make the grinder work harder. Instead reduce the number of segments on the grinding plate to increase performance.
 5. Be sure that re-tipped and new grinding plates are properly balanced.
 6. Do not run the grinder with grinding head raised any higher than necessary, i.e. tipped back on handle.
 7. Always be sure that folding handle latch is secure and has not vibrated loose after use.
 8. When grinding, the machine is exposed to high vibration. Occasionally check for fastener tightness.
-

OPERATION

The grinder is designed for both dry and wet grinding. For dry grinding, ensure a suitable industrial vacuum is connected and that operator is wearing suitable breathing respiratory equipment.

STARTING THE GRINDER

1. Check the grinding plate being used are suitable for the material being ground AND

THAT THEY ARE CORRECTLY BALANCED.

2. Check that the grinding plates being used are in good order and properly attached, with all countersunk bolts firmly in place. Check this occasionally during use, as they can work loose during operation.
3. Check that all Tri-knobs and the folding handle latch are tight and firm.
4. Raise the grinding plates from the floor.
5. Start the motor by pressing the black switch on the starter box.
6. Lower the grinding plate and commence grinding.

SHUTTING DOWN THE GRINDER

1. De-press the red stop button on the starter box.

TROUBLESHOOTING

SYMPTOM	POSSIBLE CAUSES AND CORRECTION
Grinder runs for 5-15 minutes, then stops	■ Motor thermal overload tripped. Allow to cool, and then reset thermal overloads. ■ Extension cable too long and/or not made from heavy enough cable. Get electrician to check extension lead compatibility.
Grinder runs but does not perform adequately	■ Motor defective. Repair or replace
Grinder vibrates during use	■ Grinding plates not correctly balanced. Replace or rebalance grinding plates.
Grinding noise coming from grinding head when up on jockey wheel	■ Excessively worn motor bearings. Have motor serviced.

