

# **Hire and Rental Industry Association Ltd**

Product Safety Assessment Sheet

## PLANT INFORMATION

PSA Ref #: 00010 Model No: EARLEX SM5 Plant Name: STEAM WALLPAPER STRIPPER SM5 Manufacturer: Crommelins Machinery WA Manufacturer's Website: www.crommelins.com.au Web Link for Plant: www.crommelins.com.au Mandatory Personal Protective Equipment:





Eye Protection Foot Protective Protection Clothing



## **RISK ASSESSMENT INFORMATION**

# Operator Competency: Plant Licence Not Required Potential Hazard(s) Risk Level Control Measure(s) Coming into contact with high temperature, steam, or hot parts. Medium/Low • The plant is provide over the steam tank with a pressure releabefore opening and tank. Release the perfore completely run to touch the steam Warning label on plat to safeguard agains water or steam com Electrical hazard. Medium/Low • Do not allow steam contact with power Do not use power of stripped for supply Cover any power put by moisture running equipment is tested with electrical safet Use a power supply switch. Slip/Fall Medium/Low • Maintain a sure food

## The plant is provided with a protective cover over the steam tank. The tank is provided with a pressure release cap. Allow to cool before opening and filling the steam/water tank. Release the pressure relief cap fully before completely removing the tank cap. Do not touch the steam plate or other hot parts. Warning label on plant. Wear eye protection to safeguard against possible droplets of hot water or steam coming of the steam plate.

 Do not allow steam/water to come into contact with power supply or power outlet.
 Do not use power outlet on walls being stripped for supply of electricity to the unit.
 Cover any power points likely to be affected by moisture running down the walls. Ensure equipment is tested/tagged for compliance with electrical safety testing requirements.
 Use a power supply protected by a safety switch.

 Maintain a sure footing and a stable platform when working overhead. Wear appropriate footwear when working in slippery or wet areas. Customer Identified Hazard(s)

### **Key Operating Instructions**

Fill with water only to the maximum indicated level.

Wait until the steam is flowing freely before commencing operation.

Use only H/D 15amp rated extension lead.

Connect to a power supply protected by a safety switch.

Plug in to a power source away from the area to be worked on.

Ensure cables and plugs are not in contact with wet areas.

To refill, let the unit cool down, release the pressure relief cap fully before completely removing, then fill to indicated level.

Maintain a sure footing and a stable platform if working above the floor level.

Wear appropriate footwear when working in slippery or wet conditions.

Please refer to the User Guide and Operator's Manual for Operating Instructions

The Safety Information on this assessment has been developed for the Hire and Rental Industry to assist in the safe operation of this equipment.

This information contains general information only and should not be relied upon as a substitute for professional advice, which the user should seek before operating.

Once printed this is an uncontrolled copy.